

Geocel Trade Mate Roofers Seal



Features and Benefits

- Excellent adhesion to most common roofing substrates
- One component, easy to apply and tool
- Suitable for use on damp and wet surfaces
- Cures to form a flexible seal with high movement capability
- Mildew resistant
- High gloss finish
- Can be over painted

Application

- Can be used for most roofing applications and repairs
- It will adhere to various roofing substrates including lead, bitumen and galvanised steel
- Ideal for sealing around gutters, down pipes, lead flashing and corrugated roofing

Cleaning

- Excess sealant may be cleaned off whilst in an uncured state using a dry disposable cloth
- Alcohol based solvents can be used to clean tools

Painting

- Geocel® Trade Mate Roofers Seal sealant may be painted after 24 hours, some paints may crack in dynamic joints

Packaging

- Geocel® Trade Mate Roofers Seal is supplied in 310ml cartridges packed in boxes of 12

Limitations

- Geocel® Trade Mate Roofers Seal is not suitable for surfaces that bleed oils or plasticisers
- It should be ensured that the sealant is compatible with the substrates to which it is being applied

Description

Geocel® Trade Mate Roofers Seal wet or dry surface sealant is a single component, high performance elastomeric sealant and can be used for most roofing applications and repairs. It will adhere to various roofing substrates including lead, bitumen and galvanised steel. Ideal for sealing around gutters, down pipes, lead flashing and corrugated roofing.

Finishing

When applied to wet surfaces tooling is necessary to ensure that a good bond with the surface is formed. Always tool down immediately following application using a spatula or a piece of wood wetted with a dilute soap solution.

Method of use

- Ensure gaps and cracks to be filled are free from dust, dirt and grease
- Remove nozzle and cut off end of cartridge
- Replace nozzle and cut the tip to the required width
- Place the cartridge in a cartridge gun and apply material into gap and crack to be filled
- Ensure Geocel® Trade Mate Roofers Seal makes full contact with the sides and back of the joint

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore tests are necessary. Our general conditions apply.

Geocel Trade Mate Roofers Seal

Technical Characteristics

Storage Life	24 months from date of manufacture when stored in temperatures below 30°
Colour	Black, Grey
Tack Free	72 hours
Cure Rate	5 days (6mm bead)
Specific Gravity	0.95
Tensile Strength	2.0Mpa
Elongation	800%
Service Temperature	-40°C to +80°

Health and Safety

- Health and Safety data sheets available on request

Technical Service

- For further technical information, advice on suitability for specific applications, or detailed Health and Safety information, contact Geocel® Technical Service

Manufactured under ISO 9001

This technical data sheet replaces all previous editions. The data on this sheet have been compiled according to the last laboratory report. Technical characteristics can be changed or adapted. We are not responsible for any incomplete information. Before use, one needs to ensure that the product is suitable for his application. Therefore tests are necessary. Our general conditions apply.